<u>HIREDEPOT</u> <u>Chain Block – HAZARD ASSESSMENT</u>

The Identified Hazard	Risk Yes/ No	The Proposed Method of Control Measure	Are The Control Methods Practical
Persons could be injured if the operator performs duties that are not his responsibility and beyond the scope of his technical capabilities.	Yes	The operator should be adequately trained or licensed. The operator must not carry out any work that is outside his normal duties and report any matters of concern to his supervisor.	Yes
Entrapment in the chains and or block	Yes	Keep hands clear of any chains that are not directly needed for hoisting. Do not overload.	Yes
Crushing due to overloading or failure of the unit.	Yes	Do not overload. Daily inspection of the block and chains is required or before each use. Ensure the anchor point is secure enough to hold the intended load. Do not stand directly below the load that is being raised. Only use on vertical lifts.	Yes
Persons could be injured if the machine operator is unfamiliar with typical unsafe conditions and hazards that could affect the safe operation of the unit.	Yes	The operator should be trained in determining unsafe conditions and hazards that are relative to the machine's safe operation.	Yes
Persons could be injured if personal protective equipment is not available or being used when working in an unsatisfactory environment e.g. noise, heat, fumes, etc.	Yes	Instruct the operator to ensure that appropriate personal protective equipment is available and is in good condition prior to commencing work.	Yes

Mandatory Personal Protective Equipment:









\mathbf{C}_{1}	ustomer	Signature:	