

Operating Procedure

Demolition Saw - Petrol

Guide only

Before Starting

1. Adjust the blade protection guard to the required position.

Specifications:

Demolition saw 14" Petrol

| | |
|--------------------|-------------------------------|
| Blade Diameter: | 350 mm |
| Max cutting Depth: | 125 mm |
| Power: | 2-stroke petrol |
| Weight: | 11 kg |
| Water Supply: | Mains water required on site. |

To start the Demo saw

1. While holding both throttle triggers in, position the switch in the start position. This should hold the throttle in.
2. Prime the fuel by depressing the fuel primer 3-4 times.
3. If the engine is cold, turn the choke lever to the 'on' position.
4. Crank the pull cord, until the engine 'coughs'.
5. Turn the choke off, and then crank the pull cord until the engine starts.

Demolition saw 16" Petrol

| | |
|--------------------|-------------------------------|
| Blade Diameter: | 400 mm |
| Max cutting Depth: | 150 mm |
| Power: | 2-stroke petrol |
| Weight: | 14 kg |
| Water Supply: | Mains water required on site. |

To stop the Engine

1. Release the throttle.
2. Turn the ignition switch to the "OFF" position / depress the off button.

Trouble Shooting

| Problem | Possible Solution |
|----------------------|---|
| Demo Saw won't start | Most likely cause is that the machine is flooded. Leave to rest for 15 minutes, then start again following the procedure above. |

Mandatory Personal Protective Equipment:



Dust Mask
Protection



Foot
Protection



Hearing



Goggles
Clothing



Protective Safety

Do not under any circumstances attempt any repairs. Call your local HireDepot office.

This operating and safety brochure is intended as a guide only. It does not override license requirements nor is it suitable as an operating lesson.

If you are unsure about any aspect of the equipment, its capabilities or the correct usage, please call our trained staff for instruction or any questions you may have regarding the safe operation of this equipment.