HIREDEPOT Fall Protection – HAZARD ASSESSMENT

<u>The Identified Hazard</u>	Risk Yes/ No	The Proposed Method of Control Measure	Are the Control Methods Practical
Persons could be injured if the operator performs duties that are not his responsibility and beyond the scope of his technical capabilities.	Yes	The operator should be adequately trained or licensed. The operator must not carry out any work that is outside his normal duties and report any matters of concern to his supervisor. Thoroughly read and understand the user's guide and all other safety information.	Yes
Persons could be injured if the equipment is not suitably anchored, or set up properly.	Yes	Take time and care to read the instructions properly. Ensure the anchor point is suitable to hold the force generated from a fall. Always use a tethered restraint.	Yes
Persons could be injured when working on roofs or elevated heights, due to unsuitable weather conditions.	Yes	The operator should determine whether or not the workplace is suitable for safe operation. Do not work on wet or slippery roofs, or in high winds.	Yes
Persons could be injured if the surface is unsuitable for working safely on.	Yes	Persons should adequately assess the type of material that they will be working on. Do not walk on/ over cement sheeting, skylights, fibreglass roof sheeting etc.	Yes
Persons could be injured if the equipment they are using is faulty.	Yes	It is the responsibility of the operator to inspect all pieces of equipment and carry out the relevant safety checks. If a fault is found, tag immediately and do not use. Notify staff as soon as possible.	Yes
Persons could be injured if the operator performs duties that are not his responsibility and beyond the scope of his technical capabilities.	Yes	The operator should be instructed not to carry out any work that is outside his normal duties and report any matters of concern to his supervisors.	Yes

Customer Signature: _____