

## Block grab

IDENTIFIED HAZARD	RISK (YES / NO)	PROPOSED METHOD OF CONTROL MEASURE	ARE THE CONTROL METHODS PRACTICAL?
Persons could be injured if the operator performs duties that are not his responsibility and beyond the scope of his technical capabilities.	YES	The operator should be adequately trained or licensed. The operator must not carry out any work that is outside his normal duties and report any matters of concern to his supervisor.	YES
Persons could be injured if they trap fingers or other body parts in articulated arms.	YES	The operator must avoid manually handling the grab whilst articulating. Operator should be wearing gloves.	YES
Persons could be injured or killed if the load falls from the grab.	YES	Grab must be inspected before use and in service for any signs of mechanical wear or damage to the grip pads. Loads must never be lifted over people. SWL of lifting plant must never be exceeded. All slings, chains etc. must never be exceeded. All slings, chains etc. must have sufficient capacity and be in serviceable condition.	YES
Persons could be injured if they are crushed by the load or equipment.	YES	The working environment must be checked to ensure it is satisfactory for stable use of equipment. Operators should be outside of swing radius of suspended loads (use rope or similar to guide load).	YES

### MANDATORY PERSONAL PROTECTIVE EQUIPMENT



Customer Signature: \_\_\_\_\_

Date: \_\_\_\_\_