

Chainsaw

(Guide only)

BEFORE STARTING

1. Read and understand the hazard assessment sheet.
2. Do not use extension leads longer than 20 metres.

PLEASE NOTE: Chainsaws are very dangerous pieces of equipment when not used properly. Always take care when using a chainsaw. Operators should not perform duties beyond their capabilities.

REPLACING THE CHAIN

1. Loosen the chain tensioner screw.
2. Undo the chain assembly cover on side of machine.
3. Remove the chain and bar.
4. Mount new chain on bar, taking care to place chain on, in the right direction. Put chain and bar back onto chainsaw.
5. Place cover back on and put nuts holding cover on finger tight.
6. Adjust the chain tensioner screw, so the chain is at the correct tension.
7. Tighten the nuts that hold the cover on.

TO START THE ENGINE (PETROL MODELS)

1. While holding both throttle triggers in, position the switch in the 'choke' position, (the bottom most switch). This should hold the throttle in.
2. Crank the pull cord, until the engine 'coughs'.
3. Flick the switch up one position and then crank the pull cord until the engine starts.

MANDATORY PERSONAL PROTECTIVE EQUIPMENT



TROUBLESHOOTING

Problem	Possible solution

Do not under any circumstances attempt any repairs. Please call your local Hiredepot branch for assistance.

This operating and safety brochure is intended as a guide only for the safe operation of this equipment. It does not override license requirements nor is it a substitute for structured operating lesson. If you are unsure about any aspect of the equipment, its capabilities or the correct usage, please call our trained staff for instruction or any questions you may have regarding the safe operation of this equipment.