

## Demolition saw (petrol)

(Guide only)

### BEFORE STARTING

1. Read and understand the hazard assessment sheet.
2. Adjust the blade protection guard to the required position.

### TO START THE DEMO SAW

1. While holding both throttle triggers in, position the switch in the start position. This should hold the throttle in.
2. Prime the fuel by depressing the fuel primer 3-4 times.
3. If the engine is cold, turn the choke lever to the 'on' position.
4. Crank the pull cord, until the engine 'coughs'.
5. Turn the choke off, and then crank the pull cord until the engine starts.

### TO STOP THE DEMO SAW

1. Release the throttle.
2. Turn the ignition switch to the "OFF" position / depress the off button.

SPECIFICATIONS (Demolition saw 14" petrol)	
Blade diameter	350 mm
Max cutting depth	125 mm
Power	2-stroke petrol
Weight	11kg
Water supply	Mains water required on site

SPECIFICATIONS (Demolition saw 16" petrol)	
Blade diameter	400 mm
Max cutting depth	150 mm
Power	2-stroke petrol
Weight	14kg
Water supply	Mains water required on site

### MANDATORY PERSONAL PROTECTIVE EQUIPMENT



TROUBLESHOOTING	
Problem	Possible solution
Demolition saw won't start	Most likely cause is that the machine is flooded. Leave to rest for 15 minutes, then start again following the procedure above.

**Do not under any circumstances attempt any repairs. Please call your local Hiredepot branch for assistance.**

This operating and safety brochure is intended as a guide only for the safe operation of this equipment. It does not override license requirements nor is it a substitute for structured operating lesson. If you are unsure about any aspect of the equipment, its capabilities or the correct usage, please call our trained staff for instruction or any questions you may have regarding the safe operation of this equipment.