HAZARD ASSESSMENT

HIRE DEPOT

Fall protection

| IDENTIFIED HAZARD | RISK (YES/ NO) | PROPOSED METHOD OF CONTROL MEASURE | ARE THE CONTROL METHODS PRACTICAL? |
|--|----------------------|--|---|
| Persons could be injured if the operator performs duties that are not his responsibility and beyond the scope of his technical capabilities. | YES | The operator should be adequately trained or licensed. The operator must not carry out any work that is outside his normal duties and report any matters of concern to his supervisor. Thoroughly read and understand the user's guide and all other safety information. | YES |
| Persons could be injured if the anchor is not securely attached to the roof or not set up properly. | YES | Take time and care to read the instructions properly. Ensure the beam that the anchor is attached so is in suitable condition and that the harness or rope being used is securely attached also. | YES |
| Persons could be injured when working on roofs or elevated heights, due to unsuitable weather conditions. | YES | The operator should determine whether or not the workplace is suitable for safe operation. Do not work on wet or slippery roofs, or in high winds. | YES |
| Persons could be injured if the surface is unsuitable for working safely on. | YES | Persons should adequately assess the type of material that they will be working on. Do not walk on/ over cement sheeting, skylights, fibreglass roof sheeting etc. | YES |
| Persons could be injured if the equipment they are using is faulty. | YES | It is the responsibility of the operator to inspect all pieces of equipment and carry out the relevant safety checks. If a fault is found, tag immediately and do not use. Notify staff as soon as possible. | YES |

| Customer Signature: | Date: |
|---------------------|-------|
| | |