

## Demolition saw (petrol) TS910i

(Guide only)

### BEFORE STARTING

1. Read and understand the hazard assessment sheet.
2. Adjust the blade protection guard to the required position.

### TO START THE DEMO SAW

1. Prime the fuel by depressing the fuel primer 3-4 times.
2. Crank the pull cord until the engine starts.

### TO STOP THE DEMO SAW

1. Release the throttle.
2. Flick the ignition switch to 'OFF' position.

SPECIFICATIONS (Demolition saw 16" petrol)	
Blade diameter	400 mm
Max cutting depth	150 mm
Power	2-stroke petrol
Weight	14kg
Water supply	Mains water required on site

### MANDATORY PERSONAL PROTECTIVE EQUIPMENT



### IMPORTANT: DON'T COST YOURSELF MORE \$\$\$

To ensure you do not cause damage to the machine and cost yourself more money than you need to, please ensure you take note of the guide lines below:

DO NOT:	REASON WHY:
USE TOO LITTLE WATER	There must be enough water to cool and lubricate the blade. This will help protect the belt from snapping and the blade from excessive wear.
POWER UP THE BLADE MID CUT	The saw should be run up to speed and kept at consistent throttle while cutting to protect the belt from snapping.
PUSH TOO HARD WHEN CUTTING	Excessive force when cutting can cause damage to the belt and blade.

### TROUBLESHOOTING

PROBLEM	POSSIBLE SOLUTION
DEMOLITION SAW WON'T START	The most likely cause is that the machine is flooded. Leave to rest for 15 minutes, then start again following the procedure above.

**Do not under any circumstances attempt any repairs. Please call your local Hiredepot branch for assistance.**

This operating and safety brochure is intended as a guide only for the safe operation of this equipment. It does not override license requirements nor is it a substitute for structured operating lesson. If you are unsure about any aspect of the equipment, its capabilities or the correct usage, please call our trained staff for instruction or any questions you may have regarding the safe operation of this equipment.